## **Technical Data**

## **BiOH**<sup>®</sup> 5450

**Description:** Bio-based polyol for use in polyurethanes. Ideal for visco-elastic foam applications.

**Shelf Life:** Shelf Life of 12 months for packaged material stored at ambient temperatures of < 100°F (38°C).

Shelf Life of 6 months for Bulk material stored at ambient temperatures of < 115°F (46°C).


**Features:** Vegetable Oil Based – Renewable raw material source.

**Regulatory Information** 

NFPA Code 1-1-0 United States, TSCA Listed HMIS Code 1-1-0 Canada, DSL Listed

## **Typical Properties:**

·	Typical Value	Based on Method
Acid Value (mg KOH/g)	0.60	AOCS Cd 3d-63
Color Gardner (GVS)	< 3	AOCS Td 1a-64
Density (g/ml)	1.00	ASTM D1298
Flash Point	> 100	ASTM D93
Hydroxyl Number (mg KOH/g)	158	ASTM E1899
Hydroxyl Type	100% secondary	Known Structure
Molecular Weight (number)	1065	Vapor Phase Osmometry
Viscosity Brookfield @ 25°C (cPs)	3300	ASTM D2196
Water (ppm)	1000	ASTM E203
Functionality	3.0	Calculated Value
<sup>2</sup> Typical Properties are not to be construed as speci	fications	



BiOH® is a registered trademark of Cargill, Incorporated

## Cargill Industrial Specialties / Box 5700 / Minneapolis, MN 55440 / 800-842-3631 / CIS\_Customerservice@cargill.com

Revision Date: 05/28/2014

All of the above product information is, to our best knowledge, true and accurate. However, since the conditions of use of this information or any material supplied are beyond our control, all recommendations or suggestions are made without guarantee, express or implied on our part. We disclaim all liability in connection with the use of the information contained herein or otherwise. Nothing contained herein shall be construed to infer freedom from patent infringement. We disclaim any implied warranty or merchant ability and any implied warranty of fitness for a particular purpose. The laws of the State of Minnesota, USA, are incorporated into and are to govern the terms of warranties.