

Choose the fluid that works harder and smarter.

Derived from over 95% rapeseed/canola oil, a renewable resource, FR3r™ natural ester is a higher performing, more reliable, and more sustainable dielectric fluid compared to mineral oil.



Exceptional reliability

- Easily handles high heat with up to 140 °C top fluid temperature limit
- Continuously dries paper insulation without creating any damaging by products or sludge for up to 8X longer paper insulation life



Increased loading capacity

- Up to 20% more loading capacity compared to mineral oil
- Design a smaller transformer with the same loading capacity, the same sized transformer with up to 20% more loading capacity, or any combination in between



More sustainable

- 100% biodegradable in as little as 10 days
- Non-toxic in water, soil, and to wildlife and humans
- Derived from >95% rapeseed oil, a renewable resource



Superior fire safety

- Over 2X higher fire and flash points compared to mineral oil
- K-class fluid with an exceptionally high fire point of 360 °C



Cost savings

- Design a more power dense transformer and save on expensive materials like steel, aluminum, copper, and insulating paper
- Eliminate downtime and save valuable resources with no maintenance needed under normal operating conditions
- Remove or greatly reduce expensive fire remediation and spill containment systems with K-class fire certification and 100% biodegradability

FR3r™
a Cargill brand

FR3r™ Natural Ester fluid properties: standard acceptance values and typical values

	Standard test methods		ASTM D6871/IEEE C57.147	IEC 62770	FR3r™ Natural Ester
PROPERTY	ASTM	ISO/IEC	As-received new fluid property requirements	Unused new fluid property requirements	TYPICAL
Physical					
Color	D1500	ISO 2211	≤1,0	-	0,5
Flash Point PMCC (°C)	D93	ISO 2719	-	≥250	260
Flash Point COC (°C)	D92	ISO 2592	≥275	-	330
Fire Point (°C)	D92	ISO 2592	≥300	≥300	360
Pour Point (°C)	D97	ISO 3016	<-10	≤-10	-33
Density at 20 °C (g/cm³)	-	ISO 3675	-	≤1,0	0,92
Relative Density (Specific Gravity) 15 °C	D1298	-	≤0,96	-	0,92
Viscosity (mm²/s)	D445	ISO 3104			
100 °C			≤15	≤15	8,0
40 °C			≤50	≤50	37
0 °C			≤500	-	225-235
-20 °C	-	-	-	-	850-950
Visual Examination	D1524	IEC 62770 4.2.1	bright and clear	clear, free from sediment and suspended matter	clear, light
Biodegradation	OECD 301B		readily biodegradable	readily biodegradable	readily biodegradable
Aquatic and Oral Acute Toxicity	OECD 202, 203, OECD 420		non-toxic	non-toxic	non-toxic
Electrical					
Dielectric Breakdown (kV)	D877	-	≥30	-	>45
Dielectric Breakdown (kV)					
1mm gap	D1816	-	≥20	-	>25
2mm gap	D1816	-	≥35	-	>50
2,5mm gap	-	IEC 60156	-	≥35	>70
Dielectric Breakdown under impulse (kV) 25,4mm gap	D3300	-	>130	-	136
Gassing Tendency (µl/min)	D2300	-	≤0	-	≤0
Dissipation Factor					
25 °C (%)	D924	-	≤0,20	-	0,010-0,15
90 °C (tan δ)	-	IEC 60247	-	≤0,05	0,01-0,03
100 °C (%)	D924	-	≤4,0	-	1,00-3,85
Chemical					
Corrosive Sulfur	D1275	IEC 62697	non-corrosive	non-corrosive	non-corrosive
Water Content (mg/kg)	D1533	IEC 60814	≤200	≤200	<50
Acid Number (mg KOH/g)	D974	IEC 62021.3	≤0,06	≤0,06	0,01-0,06
TPCB Content (mg/kg)	D4059	IEC 61619	not detectable	free from PCBs	not detectable
Total Additives	-	IEC 60666	-	Max weight fraction 5%	<2%
Oxidation Stability (48 h, 120 °C)		IEC 61125 IEC 62770			
Total Acidity (mg KOH/g)	-	IEC 62621.3	-	≤0,06	0,1-0,2
Viscosity at 40 °C (mm²/s)	-	IEC 3104	-	≤30% increase over initial	18%-25% increase
Dissipation Factor at 90 °C (tan δ)	-	IEC60247	-	≤0,05	0,1-0,2
Oxidation Induction Time 130 °C/500psi (min)	D6186	-	-	-	>94

FR3r™ fluid is fully compatible with FR3™ fluid.

* Measurement of viscosity near pour point may be inaccurate.

NOTE: Specifications should be written referencing only the defined ASTM or IEC industry standard acceptance values and test methods. The listed 'typical' values are average values summarized from a significant number of data points over many years; they are not to be identified as acceptance values.

ASTM D6871 Standard Specifications for Natural (Vegetable Oil) Ester Fluids Used in Electrical Apparatus.

IEC 62770: Fluids for electrotechnical applications – Unused natural esters liquids for transformers and similar electrical equipment.

This document is provided for your information and convenience only. All information, statements, recommendations and suggestions are believed to be true and accurate under local laws but are made without guarantee, express or implied. WE DISCLAIM, TO THE FULLEST EXTENT PERMITTED BY LAW, ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE and FREEDOM FROM INFRINGEMENT and disclaim all liability in connection with the storage, handling or use of our products or information, statements, recommendations and suggestions contained herein. All such risks are assumed by you/user. The labeling, substantiation and decision making relating to the regulatory approval status of, the labeling on and claims for your products is your responsibility. We recommend you consult regulatory and legal advisors familiar with applicable laws, rules and regulations prior to making regulatory, labeling or claims decisions for your products. The information, statements, recommendations and suggestions contained herein are subject to change without notice.

Learn more about how FR3r™ fluid can power your transformers more reliably and more sustainably at FR3rfluid.com.

